



- | |
|--|
| 1. VINYL SIDING |
| 2. WALL SHEATHING |
| 3. BOTTOM PLATE |
| 4. P.T. SILL PLATE WITH ANCHOR BOLTS AS SPECIFIED |
| 5. FLASHING |
| 6. COUNTER FLASHING |
| 7. PARGING AS SPECIFIED (MIN. 6" HIGH) |
| 8. QUAD-LOCK REGULAR 2.25" PANEL |
| 9. PEEL&STICK WATER PROOFING OR SIM. |
| 10. QUAD-LOCK TIE (6" BLUE SHOWN) |
| 11. OPTIONAL BACKFILL PROTECTION - DIMPLEBOARD OR SIM. |
| 12. BACKFILL |
| 13. GEO-TEXTILE FABRIC (OPTIONAL) |
| 14. PERIMETER DRAIN |
| 15. ALTERNATE DOWELS AND EXTEND INTO WALL AS SPECIFIED |
| 16. FOOTING STRIP - SIZE & REINFORCEMENT AS SPECIFIED |
| 17. QUAD-LOCK TRACK |
| 18. ZERO COMPACTION SAND OR GRAVEL |
| 19. UNDER SLAB INSULATION - IF REQUIRED BY CODE |
| 20. WWM OR LONG. & TRANS. REBAR FOR SLAB REINFORCEMENT |
| 21. VAPOR BARRIER AS SPECIFIED |
| 22. SLAB ON GRADE AS SPECIFIED |
| 23. REINFORCED CONCRETE CORE |
| 24. HORIZONTAL REINFORCEMENT AS SPECIFIED ALTERNATE AROUND VERTICAL BARS |
| 25. VERTICAL REINFORCEMENT AS SPECIFIED |
| 26. INTERIOR FINISH (FASTEN GYPSUM WALLBOARD TO PLASTIC FLANGES) |
| 27. SILL SEALER |



Quad-Lock Building Systems Ltd.
 7398 - 132nd Street
 Surrey, BC V3W 4M7
 Canada
 888.711.5625 - Toll Free
 604.590.3111
 604.590.8412 - fax
 www.quadlock.com

FOUNDATION PONY WALL

DATE:	2009-01-21	SCALE:	NOT TO SCALE
REVISION NO.:	R-02	PROJECT:	
REVISION DATE:	2009-07-10	CUSTOMER:	
DRAWN BY:	Z. PROSTRAN	APPROVED BY:	H.M.K. & D.J.B.
			DRAWING NO.:
			QL-118

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.
 IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.