



- 1. EXTERIOR FINISH AS SPECIFIED
- 2. QUAD-LOCK TIE (6" BLUE SHOWN)
- 3. PARAPET AS SPECIFIED
- 4. COMPACTED FILL
- 5. SLOPE GRADE AWAY FROM WALL
- 6. PEEL&STICK WATER PROOFING OR SIM.
- 7. VERTICAL REINFORCEMENT AS SPECIFIED
- 8. HORIZONTAL REINFORCEMENT AS SPECIFIED
- 9. REINFORCED CONCRETE CORE
- 10. QUAD-LOCK REGULAR 2.25" PANEL
- 11. INTERIOR FINISH (GYPSUM WALLBOARD) FASTEN TO QUAD-LOCK TIE FLANGES

- 12. MINIMUM BEARING AND BEARING PAD AS SPECIFIED
- 13. DOWEL REINFORCEMENT AS SPECIFIED
- 14. CEILING FINISH
- 15. HOLLOW CORE PRECAST PANELS
- 16. HAT CHANNEL FOR CEILING FINISH ATTACHMENT
- 17. HOLLOW CORE PANEL REINFORCEMENT
- 18. QUAD-LOCK TRACK
- 19. ALLOW CONCRETE TO INFILL THE CORES BY BREAKING OUT THE TOP OF HOLLOW CORE SKIN AT EVERY DOWEL LOCATION
- 20. CONCRETE TOPPING AS SPECIFIED



Quad-Lock Building Systems Ltd.
7398 - 132nd Street
Surrey, BC V3W 4M7
Canada
888.711.5625 - Toll Free
604.590.3111
604.590.8412 - fax
www.quadlock.com

HOLLOW CORE PANELS PERPENDICULAR TO WALL

| | | | |
|----------------|-------------|--------------|-----------------|
| DATE: | 2009-01-21 | SCALE: | NOT TO SCALE |
| REVISION NO.: | R-02 | PROJECT: | |
| REVISION DATE: | 2009-07-10 | CUSTOMER: | |
| DRAWN BY: | Z. PROSTRAN | APPROVED BY: | H.M.K. & D.J.B. |
| | | | DRAWING NO.: |
| | | | QL-305 |

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.
IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.