



1. EXTERIOR FINISH AS SPECIFIED
2. QUAD-LOCK TIE (6" BLUE SHOWN)
3. PARGING AS SPECIFIED
4. COMPACTED FILL
5. SLOPE GRADE AWAY FROM WALL
6. PEEL&STICK WATER PROOFING OR SIM.
7. VERTICAL REINFORCEMENT AS SPECIFIED
8. HORIZONTAL REINFORCEMENT AS SPECIFIED
9. REINFORCED CONCRETE CORE
10. QUAD-LOCK REGULAR 2.25" PANEL
11. INTERIOR FINISH (GYPSUM WALLBOARD) FASTEN TO QUAD-LOCK TIE FLANGES

12. MINIMUM BEARING AND BEARING PAD AS SPECIFIED
13. DOWEL REINFORCEMENT AS SPECIFIED
14. CEILING FINISH
15. HOLLOW CORE PRECAST PANELS
16. HAT CHANNEL FOR CEILING FINISH ATTACHMENT
17. HOLLOW CORE PANEL REINFORCEMENT
18. QUAD-LOCK TRACK
19. ALLOW CONCRETE TO INFILL THE CORES BY BREAKING OUT THE TOP OF HOLLOW CORE SKIN AT EVERY DOWEL LOCATION
20. CONCRETE TOPPING AS SPECIFIED

QUAD-LOCK
Building Systems Ltd.

Quad-Lock Building Systems Ltd.
7398 - 132nd Street
Surrey, BC V3W 4M7
Canada

888.711.5625 - Toll Free
604.590.3111
604.590.8412 - fax
www.quadlock.com

HOLLOW CORE PANELS PERPENDICULAR TO WALL

DATE:	2009-01-21	SCALE:	NOT TO SCALE
REVISION NO.:	R-02	PROJECT:	
REVISION DATE:	2009-07-10	CUSTOMER:	
DRAWN BY:	Z. PROSTRAN	APPROVED BY:	H.M.K. & D.J.B.
			DRAWING NO.:
			QL-305

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.

IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.