



1. EXTERIOR FINISH AS SPECIFIED
2. QUAD-LOCK TIE (6" BLUE SHOWN)
3. PARGING AS SPECIFIED
4. COMPACTED FILL
5. SLOPE GRADE AWAY FROM WALL
6. PEEL&STICK WATER PROOFING OR SIM.
7. VERTICAL REINFORCEMENT AS SPECIFIED
8. HORIZONTAL REINFORCEMENT AS SPECIFIED
9. REINFORCED CONCRETE CORE
10. QUAD-LOCK REGULAR 2.25" PANEL
11. INTERIOR FINISH (GYPSUM WALLBOARD) FASTEN TO QUAD-LOCK TIE FLANGES

12. SIMPSON ICFVL-W OR ICFVL-CW WOOD LEDGER BRACKET FOR MORE INFORMATION SEE: http://www.simpsonstrong-tie.com/products/connectors/ICFVL.asp
13. RIM TRACK
14. ATTACH JOIST TO ICFVL w/ (1) 3"X3" CLIP ANGLE w/ #10-16 SCREWS TO EACH LEG.
15. STEEL JOIST
16. SUBFLOOR AS SPECIFIED



Quad-Lock Building Systems Ltd.
7398 - 132nd Street
Surrey, BC V3W 4M7
Canada
888.711.5625 - Toll Free
604.590.3111
604.590.8412 - fax
www.quadlock.com

STEEL FLOOR JOISTS PERPENDICULAR TO WALL

DATE:	2009-01-21	SCALE:	NOT TO SCALE
REVISION NO.:	R-02	PROJECT:	
REVISION DATE:	2009-07-10	CUSTOMER:	
DRAWN BY:	Z. PROSTRAN	APPROVED BY:	H.M.K. & D.J.B.
			DRAWING NO.:
			QL-310

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.
IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.