



1.	INTERIOR WALL FINISH AS SPECIFIED
2.	REINFORCED CONCRETE CORE
3.	QUAD-LOCK REGULAR 2.25" PANEL
4.	QUAD-LOCK TIE (6" BLUE SHOWN)
5.	EXTERIOR WALL FINISH AS SPECIFIED
6.	VERTICAL REINFORCEMENT AS SPECIFIED
7.	HORIZONTAL REINFORCEMENT AS SPECIFIED
8.	STIRRUPS & LINTEL REINFORCEMENT AS SPECIFIED
9.	PRESSURE TREATED INTERNAL WOOD BUCK FOR INSET WINDOW ATTACHMENT FASTENED TO CONCRETE VIA CAST IN PLACE SCREWS ON CONTACT SIDE
10.	WINDOW FLASHING MEMBRANE
11.	METAL FLASHING
12.	CAULKING
13.	GLAZING
14.	WINDOW FRAME BY OTHERS - FASTEN TO WOOD SPACER AS SHOWN
15.	WOOD SPACER (LINER)
16.	BLOCKING
17.	SILL BUCK IS FORMED WITH 2 - 2x4'S ON EDGE TO ALLOW FOR CONCRETE MIX POUR

QUAD-LOCK
Building Systems Ltd.

Quad-Lock Building Systems Ltd.
7398 - 132nd Street
Surrey, BC V3W 4M7
Canada

888.711.5625 - Toll Free
604.590.3111
604.590.8412 - fax
www.quadlock.com

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.

IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.

HEAD & SILL WINDOW DETAIL

DATE:	2009-01-21	SCALE:	NOT TO SCALE
REVISION NO.:	R-02	PROJECT:	
REVISION DATE:	2009-07-10	CUSTOMER:	
DRAWN BY:	Z. PROSTRAN	APPROVED BY:	H.M.K. & D.J.B.
			DRAWING NO.:
			QL-407