



1.	INTERIOR FINISH (GYPSUM WALLBOARD) FASTEN TO QUAD-LOCK TIE FLANGES
2.	QUAD-LOCK REGULAR 2.25" PANEL
3.	QUAD-LOCK TIE (6" BLUE SHOWN)
4.	REINFORCED CONCRETE CORE
5.	VERTICAL REINFORCEMENT AS SPECIFIED
6.	HORIZONTAL REINFORCEMENT AS SPECIFIED
7.	PEEL&STICK WATER PROOFING OR SIM.
8.	COMPACTED FILL
9.	PARGING AS SPECIFIED
10.	STEEL ANGLE AS SPECIFIED
11.	CONTINUOUS FLASHING AS SPECIFIED
12.	FERRO ANGLE SUPPORT BRACKET W/ BOLTS CAST IN PLACE SEE http://www.ferrocorp.com/pages/fast/fast.htm FOR MORE INFORMATION
13.	INSERT FLASHING IN SAW KERF AND CAULK
14.	AIR SPACE AS SPECIFIED
15.	EXTERIOR BRICK FINISH AS SPECIFIED
16.	BRICK TIES AS SPECIFIED

QUAD-LOCK
Building Systems Ltd.

Quad-Lock Building Systems Ltd.
7398 - 132nd Street
Surrey, BC V3W 4M7
Canada

888.711.5625 - Toll Free
604.590.3111
604.590.8412 - fax
www.quadlock.com

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.
IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.

FERRO BRICK LEDGE DETAIL

DATE:	2009-01-21	SCALE:	NOT TO SCALE
REVISION NO.:	R-02	PROJECT:	
REVISION DATE:	2009-07-10	CUSTOMER:	
DRAWN BY:	Z. PROSTRAN	APPROVED BY:	H.M.K. & D.J.B.
			DRAWING NO.:
			QL-603