



1. EXTERIOR WALL FINISH
2. QUAD-LOCK REGULAR 2.25" PANEL
3. REINFORCED CONCRETE CORE
4. VERTICAL REINFORCEMENT AS SPECIFIED
5. HORIZONTAL REINFORCEMENT AS SPECIFIED
6. QUAD-LOCK TIE (6" BLUE SHOWN)
7. PVC/METAL ELECTRICAL BOX TO BE 2.25" DEEP + 1/2" FOR GYPSUM WALLBOARD
8. SHIM IF BOX IS LESS THAN 2.25" DEEP
9. CONCRETE ANCHORS
10. REMOVE FOAM AT EVERY BOX LOCATION AFTER CONCRETE CONSOLIDATES
11. GROOVE OUT QUAD-LOCK PANELS 2" DEEP WITH AN ELECTRICAL HOT KNIFE OR A HAND SAW WITH 2 BLADES OR A CHAINSAW WITH A DEPTH SPACER
12. SPRAY FOAM WIRE IN PLACE EVERY 2'-0" O.C. MAX.
13. ELECTRICAL CABLE



Quad-Lock Building Systems Ltd.
7398 - 132nd Street
Surrey, BC V3W 4M7
Canada

888.711.5625 - Toll Free
604.590.3111
604.590.8412 - fax
www.quadlock.com

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.
IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.

ELECTRICAL BOX AND WIRE DETAIL

DATE:	2009-01-21	SCALE:	NOT TO SCALE
REVISION NO.:	R-02	PROJECT:	
REVISION DATE:	2009-07-10	CUSTOMER:	
DRAWN BY:	Z. PROSTRAN	APPROVED BY:	H.M.K. & D.J.B.
			DRAWING NO.:
			QL-608