



| | |
|-----|--|
| 1. | EXTERIOR WALL FINISH |
| 2. | VERTICAL REINFORCEMENT AS SPECIFIED |
| 3. | REINFORCED CONCRETE CORE |
| 4. | QUAD-LOCK REGULAR 2.25" PANEL |
| 5. | FASTEN INTERIOR FINISH TO QUAD-LOCK TIES |
| 6. | HORIZONTAL REINFORCEMENT AS SPECIFIED |
| 7. | QUAD-LOCK TIE (8" YELLOW SHOWN) |
| 8. | PLYWOOD BASE - FASTEN TO QUAD-LOCK PLASTIC TIE FLANGES |
| 9. | FASTEN ELECTRICAL PANEL TO PLYWOOD BASE AS SHOWN |
| 10. | INSTALL QUAD-LOCK PLUS PANELS AT EVERY ELECTRICAL PANEL LOCATION |
| 11. | REMOVE FOAM AT EVERY ELECTRICAL PANEL LOCATION AFTER CONCRETE CONSOLIDATES |
| 12. | FASTEN ELECTRICAL PANEL DIRECTLY TO CONCRETE |



Quad-Lock Building Systems Ltd.
7398 - 132nd Street
Surrey, BC V3W 4M7
Canada

888.711.5625 - Toll Free
604.590.3111
604.590.8412 - fax
www.quadlock.com

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.

IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.

ELECTRICAL PANEL DETAIL

| | | | |
|----------------|-------------|--------------|-----------------|
| DATE: | 2009-01-21 | SCALE: | NOT TO SCALE |
| REVISION NO.: | R-02 | PROJECT: | |
| REVISION DATE: | 2009-07-10 | CUSTOMER: | |
| DRAWN BY: | Z. PROSTRAN | APPROVED BY: | H.M.K. & D.J.B. |
| | | | DRAWING NO.: |
| | | | QL-609 |