



1. EXTERIOR FINISH AS SPECIFIED
2. WALL SHEATHING
3. BOTTOM PLATE
4. RIM BOARD AS SPECIFIED
5. ANCHOR BOLTS AS SPECIFIED
6. PRESSURE TREATED SILL PLATE
7. SILL SEALER
8. QUAD-LOCK REGULAR 2.25" PANEL
9. PARING HEIGHT AS PER CODE (EXTEND 3" BELOW GRADE)
10. VERTICAL REINFORCEMENT AS SPECIFIED
11. HORIZONTAL REINFORCEMENT AS SPECIFIED
12. FINISHING STRIP IF REQUIRED
13. QUAD-LOCK 8" TIE YELLOW
14. OPTIONAL DRAINAGE BOARD (DELTA MS CLEAR OR EQ.)
15. PEEL & STICK WATER PROOFING OR SIM. (APPLY 24" UP THE WALL)
16. FREE DRAINING FILL
17. PERIMETER DRAIN
18. FOOTING STRIP REINFORCEMENT AS SPECIFIED
19. ALTERNATE DOWEL LEGS AS SHOWN
20. QUAD-LOCK TRACK
21. FOOTING PAD (SEE STRUCTURAL DETAILS FOR SIZE AND REINF.)
22. VAPOR BARRIER AS SPECIFIED
23. INSULATION AS SPECIFIED
24. COMPACTED FILL
25. ZERO COMPACTION SAND OR GRAVEL
26. SLAB ON GRADE
27. WELDED WIRE MESH OR LONGITUDINAL AND TRANSVERSE REBAR
28. FS PANEL FOR GYPSUM WALLBOARD ATTACHMENT
29. INTERIOR FINISH (GYPSUM WALLBOARD) FASTEN TO QUAD-LOCK TIE FLANGES
30. QUAD-LOCK WIRE TOP TIE
31. QUAD-LOCK TRACK - PROVIDES FASTENING SURFACE FOR INTERIOR FINISH
32. SPRAY FOAM INSULATION
33. ENGINEERED I-JOISTS AS SPECIFIED
34. INSULATION
35. SUBFLOOR AS SPECIFIED
36. INTERIOR FINISH
37. INSULATION & STUDS

QUAD-LOCK
Building Systems Ltd.

Quad-Lock Building Systems Ltd.
7398 - 132nd Street
Surrey, BC V3W 4M7
Canada

888.711.5625 - Toll Free
604.590.3111
604.590.8412 - fax
www.quadlock.com

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.
IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.

DAMP PROOFING DETAIL

DATE:	2009-01-21	SCALE:	NOT TO SCALE
REVISION NO.:	R-02	PROJECT:	
REVISION DATE:	2009-07-10	CUSTOMER:	
DRAWN BY:	Z. PROSTRAN	APPROVED BY:	H.M.K. & D.J.B.
			DRAWING NO.:
			QL-611