



1.	QUAD-LOCK TIE (8" YELLOW SHOWN)
2.	QUAD-LOCK REGULAR 2.25" PANEL
3.	REINFORCED CONCRETE CORE
4.	ANGLE BRACKET
5.	CUT TIE FLANGES AND INSERT AS SHOWN
6.	OUTSIDE PANELS ARE ALWAYS MITER THROUGH CENTER OF A KNOB; AFTER CUTTING REMOVE KNOB FOR ANGLE BRACKET TO FIT
7.	REBAR BEND AS SPECIFIED
8.	INSIDE WALL FORMS DO NOT REQUIRE ANGLE BRACKETS
9.	PLACE TIES AS CLOSE TO CORNER AS POSSIBLE
10.	HORIZONTAL REINFORCEMENT AS SPECIFIED ALTERNATE AROUND VERTICAL BARS
11.	VERTICAL REINFORCEMENT AS SPECIFIED



Quad-Lock Building Systems Ltd.
 7398 - 132nd Street
 Surrey, BC V3W 4M7
 Canada
 888.711.5625 - Toll Free
 604.590.3111
 604.590.8412 - fax
 www.quadlock.com

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.
 IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.

NON 90° ANGLE DETAIL

DATE:	2009-01-21	SCALE:	NOT TO SCALE
REVISION NO.:	R-02	PROJECT:	
REVISION DATE:	2009-07-10	CUSTOMER:	
DRAWN BY:	Z. PROSTRAN	APPROVED BY:	H.M.K. & D.J.B.
			DRAWING NO.:
			QL-702