



1.	BEVEL EDGE OF CONCRETE
2.	MIN = 3"; MAX = 6"
3.	PLYWOOD SPACER - TO ALLOW FOR EVEN TRANSITION OF EXTERIOR WALL FINISH TO WALL CAP
4.	SECOND FORM LAYER - FASTEN TO QUAD-LOCK TIE FLANGES AS SHOWN
5.	QUAD-LOCK REGULAR 2.25" PANEL
6.	QUAD-LOCK TIE (6" BLUE SHOWN)
7.	VERTICAL REINFORCEMENT AS SPECIFIED
8.	HORIZONTAL REINFORCEMENT AS SPECIFIED
9.	REINFORCED CONCRETE CORE

QUAD-LOCK
Building Systems Ltd.

Quad-Lock Building Systems Ltd.
7398 - 132nd Street
Surrey, BC V3W 4M7
Canada

888.711.5625 - Toll Free
604.590.3111
604.590.8412 - fax
www.quadlock.com

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.
IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.

WALL CAP DETAIL

DATE:	2009-01-21	SCALE:	NOT TO SCALE
REVISION NO.:	R-02	PROJECT:	
REVISION DATE:	2009-07-10	CUSTOMER:	
DRAWN BY:	Z. PROSTRAN	APPROVED BY:	H.M.K. & D.J.B.
			DRAWING NO.:
			QL-708