



1.	BEVEL EDGE OF CONCRETE
2.	MIN = 3"; MAX = 6"
3.	PLYWOOD SPACER - TO ALLOW FOR EVEN TRANSITION OF EXTERIOR WALL FINISH TO WALL CAP
4.	SECOND FORM LAYER - FASTEN TO QUAD-LOCK TIE FLANGES AS SHOWN
5.	QUAD-LOCK REGULAR 2.25" PANEL
6.	QUAD-LOCK TIE (6" BLUE SHOWN)
7.	VERTICAL REINFORCEMENT AS SPECIFIED
8.	HORIZONTAL REINFORCEMENT AS SPECIFIED
9.	REINFORCED CONCRETE CORE

**QUAD-LOCK**  
Building Systems Ltd.

Quad-Lock Building Systems Ltd.  
7398 - 132nd Street  
Surrey, BC V3W 4M7  
Canada

888.711.5625 - Toll Free  
604.590.3111  
604.590.8412 - fax  
www.quadlock.com

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.  
IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.

### WALL CAP DETAIL

DATE:	2009-01-21	SCALE:	NOT TO SCALE
REVISION NO.:	R-02	PROJECT:	
REVISION DATE:	2009-07-10	CUSTOMER:	
DRAWN BY:	Z. PROSTRAN	APPROVED BY:	H.M.K. & D.J.B.
			DRAWING NO.:
			QL-708