



1.	QUAD-LOCK REGULAR 2.25" PANEL
2.	QUAD-LOCK TIE (8" YELLOW SHOWN)
3.	HORIZONTAL REINFORCEMENT AS SPECIFIED
4.	VERTICAL REINFORCEMENT AS SPECIFIED
5.	SECURE ONE HALF OF A PVC PIPE TO THE QUAD-LOCK WALL BEFORE POUR
6.	EXTERIOR WALL FINISH
7.	REINFORCED CONCRETE CORE
8.	FASTEN INTERIOR WALL FINISH TO QUAD-LOCK TIE FLANGES
9.	SECURE PLUMBING ELEMENT IN PLACE WITH SPRAY FOAM, ONCE DRY RASP DOWN FLUSH WITH QUAD-LOCK PANELS



Quad-Lock Building Systems Ltd.
 7398 - 132nd Street
 Surrey, BC V3W 4M7
 Canada
 888.711.5625 - Toll Free
 604.590.3111
 604.590.8412 - fax
 www.quadlock.com

LARGE PLUMBING DETAIL

DATE:	2009-01-21	SCALE:	NOT TO SCALE
REVISION NO.:	R-02	PROJECT:	
REVISION DATE:	2009-07-10	CUSTOMER:	
DRAWN BY:	Z. PROSTRAN	APPROVED BY:	H.M.K. & D.J.B.
			DRAWING NO.:
			QL-711

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.
 IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.