



1.	EXISTING CONCRETE BLOCK (CMU) WALL
2.	GROUTED CELL
3.	PROVIDE DOWELS BETWEEN WALLS TO MATCH HORIZONTAL REBAR DRILL TO CONCRETE & SECURE W/ EPOXY GROUT LENGTH OF DOWEL SUFFICIENT TO DEVELOP PROPER SPLICE
4.	QUAD-LOCK TIE (6" BLUE SHOWN)
5.	QUAD-LOCK REGULAR 2.25" PANEL
6.	REINFORCED CONCRETE CORE
7.	HORIZONTAL REINFORCEMENT AS SPECIFIED
8.	VERTICAL REINFORCEMENT AS SPECIFIED

QUAD-LOCK
Building Systems Ltd.

Quad-Lock Building Systems Ltd.
7398 - 132nd Street
Surrey, BC V3W 4M7
Canada

888.711.5625 - Toll Free
604.590.3111
604.590.8412 - fax
www.quadlock.com

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.
IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.

QUAD-LOCK WALL ATTACHMENT TO EXISTING CORE FILLED CMU WALL

DATE:	2009-01-21	SCALE:	NOT TO SCALE
REVISION NO.:	R-02	PROJECT:	
REVISION DATE:	2009-07-10	CUSTOMER:	
DRAWN BY:	Z. PROSTRAN	APPROVED BY:	H.M.K. & D.J.B.
			DRAWING NO.:
			QL-717