



QUAD-LOCK REGULAR PANEL
ON INTERIOR & EXTERIOR
8" CONCRETE CAVITY(NOMINAL)

R-22

QUAD-LOCK REGULAR PANEL
ON INTERIOR & PLUS ON EXTERIOR
8" CONCRETE CAVITY(NOMINAL)

R-30

QUAD-LOCK PLUS PANEL
INTERIOR & EXTERIOR
8" CONCRETE CAVITY(NOMINAL)

R-38

ITEM	R-VALUE (h*ft ² *°F/BTU)	ITEM	R-VALUE (h*ft ² *°F/BTU)	ITEM	R-VALUE (h*ft ² *°F/BTU)
OUTSIDE AIR	0.25	OUTSIDE AIR	0.25	OUTSIDE AIR	0.25
STUCCO FINISH	0.78	STUCCO FINISH	0.78	STUCCO FINISH	0.78
2.25" EPS US Type IX, CAN Type III	9.79	2.25" EPS US Type IX, CAN Type III	9.79	4.25" EPS US & CAN Type II	17.4
7.75" CONCRETE CORE	.62	7.75" CONCRETE CORE	.62	7.75" CONCRETE CORE	.62
2.25" EPS US Type IX, CAN Type III	9.79	4.25" EPS US & CAN Type II	17.4	4.25" EPS US & CAN Type II	17.4
½" GYPSUM WALLBOARD	0.45	½" GYPSUM WALLBOARD	0.45	½" GYPSUM WALLBOARD	0.45
INSIDE AIR	0.68	INSIDE AIR	0.68	INSIDE AIR	0.68
TOTAL	22	TOTAL	30	TOTAL	38

QUAD-LOCK
Building Systems Ltd.

Quad-Lock Building Systems Ltd.
7398 - 132nd Street
Surrey, BC V3W 4M7
Canada

888.711.5625 - Toll Free
604.590.3111
604.590.8412 - fax
www.quadlock.com

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.
IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.

QUAD-LOCK R-VALUES

DATE:	2009-01-21	SCALE:	NOT TO SCALE
REVISION NO.:	R-02	PROJECT:	
REVISION DATE:	2009-07-10	CUSTOMER:	
DRAWN BY:	Z. PROSTRAN	APPROVED BY:	H.M.K. & D.J.B.
			QL-720