

EXTERIOR FINISH AS SPECIFIED

LAYER OF FIXING FOAM APPLIED PRIOR TO REINSERTING QUADLOCK

QUADLOCK CUT AWAY ROOFERS FELT APPLIED TO CONCRETE CORE THEN QUADLOCK REPLACED


SILICONE SEAL AT BASE OF EXTERNAL FINISH

2 INCH BY 1 INCH BATON USED FOR WALL INSTALLATION REMOVED ONCE WALL IS POURED

ROOFING FELT AS SPECIFIED

ROOF AS SPECIFIED

QUAD-LOCK[®]
Insulating Concrete Forms



Quad-Lock (England) Ltd.
Unit B3, 1 Mavis Centre
Jackfield, Shropshire
TF8 7LS

Tel : 01952 884931
Fax : 01952 883265
www.quadlock.co.uk

ROOF TO WALL SEALANT

DATE:	06/2010	SCALE:	nts
REVISION NO.:	-	PROJECT:	N/A
REVISION DATE:	-	CUSTOMER:	N/A
DRAWN BY:	M BAILEY	APPROVED BY:	
REVISED BY:	-	REVISION APPROVED BY:	
			DRAWING NO: 10.3.1

DUE TO VARIANCES IN LOCAL CODES, CONSTRUCTION PRACTICES AND REQUIREMENTS ALL DETAILS SHALL BE CONSTRUCTED IN ACCORDANCE WITH SUCH LOCAL CODES, CONSTRUCTION PRACTICES, AND REQUIREMENTS REGARDLESS OF CONSTRUCTION DETAIL SHOWN IN DRAWING. QUAD-LOCK BUILDING SYSTEMS LTD. RESERVES THE RIGHT TO CHANGE INFORMATION SHOWN WITHOUT NOTICE.